

Decal Application Instructions:

Before you begin, make sure application surface is clean and dry. Application surface temperature should be between 50 and 80 degrees.



1. The decal consists of individual vinyl letters on a paper backing, with transfer tape on the face. The transfer tape allows all the words to be applied at one time.



2. Put a piece of masking tape on each of the top corners of the decal for positioning.



3. Using a ruler or tape measure, line up the decal along a straight line on the vehicle.



4. When the decal is in place, apply a strip of masking tape along the length at the top. This acts as a hinge.



5. Lift up the decal, so that letter can be seen upside down.



6. Slowly and carefully lift up the corner of the paper backing from the letters & transfer tape. Continue to remove the paper slowly. *If a letter begins to lift off of the tape, lay the paper back down and rub to transfer the letter back to the tape.



7. With one hand, hold up the transfer tape to prevent it from folding over.



8. Holding the top two corners of the transfer tape, turn the decal over.



9. With one hand, hold the transfer tape down but away from the surface. With the other hand, stick the other bottom corner to the surface to keep the paper from curling.



10. Hold the transfer tape as you squeegee downward from the top edge, always going back to the top on the next stroke. Overlap strokes to insure complete adhesion.



11. Slowly peel off the transfer tape, removing it from the letters, while keeping your fingers within an inch of the letters.



12. Done!